SILVERLINK 600



CG6/N - Lincat Silverlink 600 Natural Gas Countertop Chargrill - W 600 mm - 16.4 kW

Create that distinctive chargrilled flavour and branded appearance without the need for messy lava rocks with the Silverlink 600 Gas Chargrill.

- Uses radiants which replaces the need for using messy lava rocks
- Twin zones for maximum flexibility
- The variable heat control and heat retaining cooking grids produce the clean, sharp chargrilled marks
- Splashguard to project surrounding surfaces from splashes
- Removable branding bars to allow for easy cleaning and access
- Drip drawer to collect all the cooking liquids to reduce cleaning times

Sp	ecif	ica	tio	ns

Specifications				
Summary		Power and Performance		
Brand	Lincat	BTU per Hour	55,956	
Range	Silverlink 600	Total Power kW	16.4	
Power Type	Gas	Cooking Area (Width x Depth) mm	477 × 440	
Gas Type	Natural Gas	Temperature Control	Mechanical	
Unit Type	Counter-top			
Available in UK Only	No			
UK Warranty	2 Years Parts and Labour Warranty			
Export Warranty	Contact your local dealer			
GTIN	5056105104544			
Key Specifications		Capacity		

Key Specifications		Capacity	
Number of Heat Zones	2	Product Output per Hour	90 x 115g [4oz] burgers [frozen]
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	414	Requires Installation	Yes
Unit Width (External) mm	600	Requires Electrical Supply	No
Unit Depth (External) mm	652	Gas Connection BSP	1/2"
Net Weight Kg	35.3	Gas Consumption at full rate Natural m³ per Hour	1.56
		Gas Pressure Natural mbar	20
		Total heat input at full rate Natural kW	14.3
		Total heat input at full rate Natural BTU per hour	48,800
Shinning			

hipping


Packed Weight Kg	38.83
Packed Height cm	63.5
Packed Width cm	70
Packed Depth cm	70


Available Accessories


CH01	Caterflex Hose 1/2" - 1 Metre - for use with units up to 66,000 BTU
CH02	Caterflex Hose 1/2" - 1.5 Metre - for use with units up to 56,000 BTU
CN6	Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm
SLS6	Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm

SILVERLINK 600

Technical Picture









Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm