



Opus 800

PRODUCT OPTIONS AND ACCESSORIES

- BA83 BASKET SMALL
- LK02 OPUS 350 LEG KIT
- OA8954 SPLASHGUARD FOR OPUS 800 ELECTRIC FRYERS

PRODUCT FEATURES

- Accurate thermostatic control up to 190°C for consistent results and safe operation
- Two stage filtration extends oil life by up to 75% and so reducing oil costs
- Oil can be filtered during or after service even whilst hot
- Hinged, lift out element, with safety interlock for easy tank access and cleaning
- Supplied with a hose and lance for easy discharge of used oil into a container

Fry delicious food accurately with this Opus 800 Single-Tank Free Standing Electric Fryer which comes with a pumped oil system which allows the oil to be filtered and ready to use again in less than five minutes. The two-stage filtration system not only extends oil life by up to 75%, but also saves you money. Boasting a precise thermostatic control, the fryer is ideal for a variety of busy commercial kitchens, whether it's a large pub or a restaurant. The hinged, lift out element with safety interlock makes it easy to access and clean the tank.

A/A FILE NUMBER:

ITEM NUMBER:



LINCAT OPUS ELECTRIC FREE-STANDING SINGLE TANK FRYER WITH PUMPED FILTRATION - 2 BASKETS - W 600 MM - 22.0 KW

MODEL: OE8108/OP

WEIGHTS & DIMENSIONS

Width	600 mil
Depth	800 mil
Height	1070 mil
Weight	102.1 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	85 cm
Ship Height	122 cm
Ship Weight	112.31 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS

Primary Energy Source Type	Electricity	Number of Electrical Conductor Wires	1
Electrical Amps	L1/L2/L3= 31.8 [1 cab]; L1/L2/L3= 2 x 15.9 [2 cab]	Electrical Connection Type	Direct Hardwired
Electrical Voltage	400 volts	Electrical Plug Type	Hardwired
Electrical Watts	22000	Number of Electrical Plugs	Not Applicable
Electrical Phase	Three	Dedicated Circuit Required	Yes
Kilowatts	22 kW	Energy Saving	No

ADDITIONAL SPECIFICATIONS

Auto Oil Top-Off	No	Number of Baskets	2
Basket Lift Type	Not Applicable	Number of Burners	Not Applicable
Control Type	Mechanical	Number of Vats (batteries)	1
Filter Media Type (if applicable)	2-Stage: Fine Tissue Filter and Stainless Steel Filter	Total Oil Capacity (volume)	36.5 l
Food Production Rate	50.2kg chips - 12mm [frozen], 65.5kg chips - 12mm [chilled] per hour	Oil Reclamation	No
Fryer Type	Open Pot	Oil Temperature Control	Mechanical
Integrated Filtration	Yes	Pumped Oil Filtration	Yes
		Split Pot	No
		Temperature Maximum	190 °C
		Temperature Minimum	90 °C
		Vat 1 Oil Capacity (volume)	36.5 l

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated
January 23, 2024

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

