

LINCAT SPECIALIST ELECTRIC COUNTER-TOP PIZZA OVEN - TWIN-DECK - W 966 MM - 8.4 KW

MODEL: PO430-2



Transport yourself to the Centro Storico district of Naples with the authentic taste of the pizzas from the Lincat Twin-Deck Electric Pizza Oven. Ideal for cafes and snack bars, the oven is designed to bake deep pan, thin crust, fresh dough, part baked or frozen pizzas, as well as a variety of other foods such as ciabatta, naan and garlic bread. With a firebrick base for that authentic, crisp taste, and a maximum temperature of 480°C, the oven also has internal illumination for better visibility of the product and enhanced appearance in front of house applications.

Lincat Specialist

PRODUCT OPTIONS AND ACCESSORIES

PO430/FS PO430 FLOORSTAND

PRODUCT FEATURES

- Ideal for restaurants, pizzerias, takeaways, fast food outlets, canteens and leisure establishments
- Perfect for deep pan, thin crust, fresh dough, part baked or frozen pizzas, as well as a variety of other foods such as ciabatta, naan, garlic bread, lasagna, jacket potatoes, pies, pasties and pastries
- Internal illumination for better visibility of product and enhanced appearance in front of house applications
- Firebrick base for crisp, even cooking of pizza bases and a maximum temperature of 400°C
- Independent controls for each deck. Independently controlled top and base of oven compartment for each deck
- Thermostatic control and temperature display gauge to monitor oven temperature more accurately
- Double-glazed door construction for energy efficiency with toughened glass for safety
- 20 minute audible timer







LINCAT SPECIALIST ELECTRIC COUNTER-TOP PIZZA OVEN - TWIN-**DECK - W 966 MM - 8.4 KW**

MODEL: PO430-2

WEIGHTS & DIMENSIONS	
Width	966 mil
Depth	925 mil
Height	665 mil
Weight	150.4 kg

SHIPPING DETAILS	
Ship Width	110 cm
Ship Depth	97 cm
Ship Height	96 cm
Ship Weight	165.44 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS	
Primary Energy Source Type	Electricity
Electrical Amps	Single Phase 36.6/Three Phase L1=12.2; L2=12.2; L3=12.2
Electrical Voltage	230 400 volts
Electrical Watts	8400
Electrical Phase	Single, Three
Kilowatts	8.4 kW

Number of Electrical Conductor Wires	1
Electrical Connection Type	Direct Hardwired
Electrical Plug Type	Hardwired
Number of Electrical Plugs	Not Applicable
Dedicated Circuit Required	Yes
Energy Saving	No

ADDITIONAL SPECIFICATIONS	
Brick Lined	Yes
Control Type	Rotary Control Knob
Cooking Chamber Depth	640 mm
Cooking Chamber Height	160 mm
Cooking Chamber Width	630 mm
Deck Cooking Depth	640 mm
Deck Cooking Height Chamber 1	160 mm
Deck Cooking Width	630 mm
Deck Material	Brick

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024







MODEL: PO430-2


BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024

