SILVERLINK 600



HC3 - Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 300 mm - 0.25 kW Designed to suite with other products in the Silverlink 600 range, the Heated Pedestal features an on/off switch and thermostatic control, making it ideal as a plate warmer.

- Designed to suite with the Silverlink 600 range
- Features an on/off switch and thermostatic control, making them ideal as plate warmers
- Silverlink 600 counter-top units are securely attached to pedestals by means of fixing screws supplied
- Adjustable shelf provides flexibility for storing bulky items
- Adjustable legs for perfect alignment even on uneven floors

Sp	ecif	ıcai	IOI	ns

Total Power kW Temperature Range °C Temperature Control	0.25 70[constant] Mechanical
•	
Temperature Control	Mechanical
	Weights and Dimensions

Key Specifications		Weights and Dimensions	Weights and Dimensions	
Number of Shelves included	1	Unit Height (External) mm 660		
Number of Shelf Positions	3	Unit Width (External) mm 300		
		Unit Depth (External) mm 600		
		Height (Internal) mm 456		
		Width (Internal) mm 298		
		Depth (Internal) mm 567		
		Shelf Dimensions Width mm 250		
		Shelf Dimensions Depth mm 530		
		Net Weight Kg 14.8		
Supply Connections		Shipping		


Supply Connections		Shipping	
Requires Installation	No	Packed Weight Kg	16.28
Requires Electrical Supply	Yes	Packed Height cm	49.5
UK 3 Pin Plug	Yes	Packed Width cm	70
Requires Hardwiring	No	Packed Depth cm	70
Electrical Supply Rating Watts	250		
Single Phase Amps	1.1		
Single Phase Voltage	230		


Available Accessories


PSH3 300 PEDESTAL SHELF

SILVERLINK 600

Technical Picture









Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm