
313161**PCGM12FG9/3****FREESTANDING 3-BURNER GAS BOILING TOP WITH
CAST IRON GRIDS ON OPEN CABINET**



- Freestanding 3-burner gas boiling top on an open cabinet (120x45 cm).
- High-efficiency cast iron burners and flame spreaders: 1 single ring (5.5 kW) and 2 double ring (9.0 kW).
- Mosaico90 is a special line of modular units, 45 cm deep, which combine perfectly with the Tecno90 range to create compact cooking islands designed to make the best use of space.
- AISI 304 stainless steel worktop (20/10 thick) with Scotch Brite finish, set up for internal coupling without external joints.
- AISI 304 stainless steel control panel and side panels.
- Deep drawn worktops with rounded corners and overflow-proof grooves for maximum hygiene and easy cleaning.
- Main burner ignition by means of a pilot burner with safety thermocouple.
- Valved gas cock.
- Enamelled cast iron pan support grid to resist acids, acids, alkalis and flames.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- The gas appliances are certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is included, should conversion on site be necessary.

TECHNICAL DATA

TOTAL POWER	23,5 kW	GAS POWER	23,5 kW
OPEN BURNER POWER	1X5,5 + 2X9 n°- kW	BOILING TOP POWER	23,5 kW
NATURAL GAS CONSUMPTION	2,48 m³/h	LPG CONSUMPTION	1.85 m³/h
CABINET DIMENSIONS	113X34X39,5 cm	NUMBER OF BURNERS	n° 3
BOILING PAN SUPPORT	RAAF enamelled cast iron	CE GAS CERTIFICATE NUMBER	CE-0085CR0045
GAS CONNECTION DIAMETER	1/2" G EN10226-1	GAS CONNECTION HEIGHT (H)	486 mm
GAS CONNECTION HEIGHT (X)	122 mm	GAS CONNECTION HEIGHT (Y)	-45 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
IPX RATING	4	WIDTH	120 cm
DEPTH	45 cm	HEIGHT	90 cm
PACKAGE WIDTH	126 cm	PACKAGE DEPTH	53 cm
PACKAGE HEIGHT	115 cm	NET WEIGHT	68 kg
GROSS WEIGHT	79,5 kg	VOLUME	0,76 m³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	2820.0 W
SENSIBLE HEAT RELEASE	7050.0 W	STEAM RELEASE	4136.0 g/h

ACCESSORIES

319002 STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90

INSTALLATION SCHEMES

