

Mod. **TL2EN NO TOP**

FR2W121D00021



MAIN FEATURES

External panels and doors in AISI 304 18/10 stainless steel (with Scotch-Brite satin finish)

External base, back and top in AISI 430

Inner in stainless steel with rounded corners

Insulation in high density (42 kg/m³ approx.) expanded polyurethane, 50 mm thick, HCFC-free

Copper-aluminum evaporator with cathaphoresis anti-corrosion treatment

High performance copper-aluminum condenser

Heating element in the door frame

Ergonomic handle throughout full width of door/drawer and magnetic seals on all four sides

Stainless steel feet Ø 2" with adjustable H 145÷205 mm

Self-closing door with block in open position at 100°

INTERNAL SETUP:

Snap-in type AISI 304 18/10 stainless steel slides and uprights, completely removable without the need of tools to facilitate cleaning

8 pairs of guides and one EN grid (600 x 800mm) each entire door compartment

COOLING SYSTEM:

High-ventilation evaporator to ensure the highest efficiency of the cooling system

Compressor and condenser that can be removed from above for simple and easy maintenance or replacement

R134a refrigerant

Automatic defrosting via electric heating element

Automatic evaporation of condensate via compressor coil on models TR or electric heating element on models TPR

CONTROLS AND SAFETY DEVICES:

Patented control able to maintain the correct degree of humidity and internal temperature of the Coldroom in order to create the ideal microclimate for the leavening process

Microprocessor control with n° 2 probes (Coldroom and end defrost) of PTC type

Defrosting with the insertion of an electrical heater, only in case of freezing evaporator

Compressor protected by termic overload cut-out with automatic reset

HUMIDITY REGULATION

The inside humidity value (UR%) is controlled by the microprocessor, through an algorithm which guarantees the correct set value

For the production of humidity the appliance need a water connection

VERSIONS / ACCESSORIES (OPTIONALS):

With working top

With working top and upstand

Mod. **TL2EN NO TOP**

FR2W121D00021

Remote condensing unit
Water cooled condenser
Revolving castors
Door lock and key

Mod. **TL2EN NO TOP**

FR2W121D00021

MODELLO:		TL2EN NO TOP
NET WIDTH	mm	1408
NET DEPTH	mm	790
90° OPENING DOOR DEPTH	mm	1280
NET HEIGHT	mm	850
NET WEIGHT	Kg	150
GROSS WIDTH	mm	1458
GROSS DEPTH	mm	850
HEIGHT GROSS	mm	900
GROSS WEIGHT	Kg	166
GROSS VOLUME	m ³	1.12
INSULATION THICKNESS	mm	50
N° OF COMPARTMENTS	n°	2
N° OF DOORS	n°	2
POWER SUPPLY		230/1/50
MAX DISTANCE EQUIVALENT CONNECTION	m	15
CAPACITY	Lt	444
PITCH	mm	55
LOADING CAPACITY n° TRAYS EN	n°	2
REFRIGERANT	gas	R134a
NOMINAL CURRENT	A	2.2
DEFROST TYPE		elettric
ABSORBED ELECTRICAL POWER	W	360
COOLING POWER	W	304
NOIS LEVEL	dB(A)	< 70
QUANTITY CHARGE GAS	g	230

(*) Evap. Temperature -10°C - Cond. temperature +55°C