



SD422L32G0 - FriFri Super Easy 422 Electric Drop-in Twin Tank Fryer with Filtration - 2 Baskets - W 400 mm - 2 x 7.5 kW When budget is a primary consideration, FriFri's unrivalled credentials, know-how and quality are still well within your reach. A drop in Super Easy 422 offers outstanding value with no compromise in quality or performance.

- Outstanding quality with no compromise in quality or performance.
- Mechanical thermostat maintains oil to within +/-8 °C of the temperature selected.
- Low watts density element with a large surface area in contact with the oil for fast recovery time and to prevent scorching which degrades oil.
- Keeping your oil in peak condition! Integral gravity filtration extends oil life by up to 75% saving you money on oil purchase and disposal costs. Optional xFri© filters the oil at the push of a button and returns oil to the tank. Filter the oil safely, even while it's still hot, mid service if necessary, and resume frying in minutes so easy there is no excuse not to!
- Pressed tank for strength and durability. Radiused corners for easy cleaning. Hinged elements with two tilt positions for draining and cleaning.
- Optimum Allergy Control. Supplied with separate oil buckets, and can be supplied with separate pumped filtration systems, providing completely segregated gravity filtration for optimum allergen control or to cater for dietary preferences.

## **Specifications**

Specifications				
Summary		Power and Performance		
Brand	FriFri	Total Power kW	2×7.5	
Range	Super Easy	Temperature Range °C	95-190	
Power Type	Electric	IP Rating	IPX4	
Unit Type	Drop in	Temperature Control	Mechanical	
Available in UK Only	No			
UK Warranty	2 Years Parts and Labour Warranty			
Export Warranty	Contact your local dealer			
GTIN	5056105123620			
Key Specifications		Capacity		
Number of Baskets	2	Product Output per Hour	2 x 17kg fries - 7mm [frozen]	
Number of Tanks	2	Capacity Litres	2 x 7.5-9.0	

 Number of Baskets
 2
 Product Output per Hour
 2x17kg fries - 7mm [frozen]

 Number of Tanks
 2
 Capacity Litres
 2x7.5-9.0

 Gravity Filtration
 Yes

 Pumped Filtration
 No

 Drain Location
 Through the body





Weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	849	Requires Installation	Yes	
Unit Width (External) mm	397.5	Requires Electrical Supply	Yes	
Unit Depth (External) mm	630	UK 3 Pin Plug	No	
Net Weight Kg	32	Requires Hardwiring	Yes	
		Electrical Supply Rating Watts	2×7,500	
		Three Phase Amps	L1=2 × 10.9; L2=2 × 10.9; L3=2 × 10.9	
		Three Phase Voltage	400	
		Number of Supply Cables	2	

Shipping

 Packed Weight Kg
 35.2

 Packed Height cm
 72

 Packed Width cm
 89

 Packed Depth cm
 80

## **Available Options**

Oil Pump

 OP1
 10il Pump

 OP2
 2 0il Pumps



**Lincat Limited** 

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

**Company No:** 2175448

A member company of

**Customer Care** 

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

**Export Customers** 

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

**Opening Hours** 

Monday - Friday:

8.30am - 5pm