



manhattan • chilled display well

- Flat bed chilled well, which is perfect for the display of salads, drinks and fruit.
- Gentle flow of convected air maintains pre-chilled food at a safe regulated temperature.
- The angle of the display deck can be adjusted for enhanced presentation.
- Gantry mounted controller installed on operators side (GO) as standard.
- The gantry controller can be installed on customer side (GC) on request.
- A wide range of optional extras are available for this display.

Stock Code	Capacity (gn)	Overall Size (mm)	Weight (kg)	Wattage (kw)	List Price (£)
MCW2-GO	2/1	825 x 660 x 560h	91	1.4	3300
MCW3-GO	3/1	1175 x 660 x 560h	108	1.7	3642
MCW4-GO	4/1	1525 x 660 x 560h	128	1.9	3925
MCW5-GO	5/1	1875 x 660 x 560h	141	1.9	4205
MCW6-GO	6/1	2225 x 660 x 560h	158	2.2	4734

manhattan • chilled display deck

- Flat bed chilled deck, which is perfect for the display of salads, drinks and fruit.
- Gentle flow of convected air maintains pre-chilled food at a safe regulated temperature.
- The angle of the display deck can be adjusted for enhanced presentation.
- Raised rear preparation shelf and glass riser to retain chilled air.
- Gantry mounted controller installed on operators side (GO) as standard.
- The gantry controller can be installed on customer side (GC) on request.
- A wide range of optional extras are available for this display.

Stock Code	Capacity (gn)	Overall Size (mm)	Weight (kg)	Wattage (kw)	List Price (£)
MCDK2-GO	2/1	825 x 764 x 560h	124	1.4	3670
MCDK3-GO	3/1	1175 x 764 x 560h	142	1.7	4090
MCDK4-GO	4/1	1525 x 764 x 560h	168	1.9	4400
MCDK5-GO	5/1	1875 x 764 x 560h	181	1.9	4715
MCDK6-GO	6/1	2225 x 764 x 560h	198	2.2	5335

manhattan • chilled display island well

- Flat bed chilled deck, which is perfect for the display of salads, drinks and fruit.
- Gentle flow of convected air maintains pre-chilled food at a safe regulated temperature.
- The angle of the display deck can be adjusted for enhanced presentation.
- Double-sided sneeze guard that can be accessed from both sides.
- A wide version is also available, which increases the depth to 810mm.
- Gantry mounted controller installed on operators side (GO) as standard.
- The gantry controller can be installed on customer side (GC) on request.
- A wide range of optional extras are available for this display.

Stock Code	Capacity (gn)	Overall Size (mm)	Weight (kg)	Wattage (kw)	List Price (£)
Chilled Island Well					
MCIW2-GO	2/1	825 x 660 x 560h	103	1.4	3885
MCIW3-GO	3/1	1175 x 660 x 560h	120	1.7	4300
MCIW4-GO	4/1	1525 x 660 x 560h	133	1.7	4630
MCIW5-GO	5/1	1875 x 660 x 560h	147	1.7	4980
MCIW6-GO	6/1	2225 x 660 x 560h	160	2.2	5580

Stock Code	Capacity (gn)	Overall Size (mm)	Weight (kg)	Wattage (kw)	List Price (£)
Chilled Wide Island Well					
MCWIW3-GO	3/1	1175 x 810 x 560h	140	1.7	4550
MCWIW4-GO	4/1	1525 x 810 x 560h	160	1.9	4925
MCWIW5-GO	5/1	1875 x 810 x 560h	180	1.9	5280
MCWIW6-GO	6/1	2225 x 810 x 560h	200	2.2	5915



Image: MCW4-GO



Image: MCDK4-GO



Image: MCIW4-GO