

Caratteristiche tecniche

Technical data

ELITE

	400 410	503 ABS	4SA	4SB	4SC	6 2P/S 6 2P/S ABS
Alimentazione elettrica Electric supply	1x230 V/ 50 Hz	3x230-400V +N/ 50Hz	3x230-400V +N/ 50Hz	3x230-400V +N/ 50Hz	3x230-400V +N/ 50Hz	3x230-400V +N/ 50Hz
Potenza pompa lavaggio Wash pump power	Kw 0,45 (HP 0,60)	Kw 0,75 (HP 1)	Kw 1,5 (2x1 HP)	Kw 0,75 (HP 1)	Kw 1,5 (2x1 HP)	Kw 1,5 (2x1 HP)
Portata pompa lavaggio Wash pump flow rate	lt. 240/min	lt. 420/min	lt. 840/min	lt. 420/min	lt. 840/min	lt. 840/min
Resistenza boiler Boiler element	W 2700	W 6000	W 6000 (W 9000)	W 6000	W 9000	W 9000
Resistenza vasca Tank element	W 1800	W 2200	W 4500	W 2200	W 4500	W 4500
Potenza massima assorbita Total power rating	W 3150	W 6750	W 7500 (W 10500)	W 6750	W 10500	W 10500
Capacità vasca Wash tank capacity	lt. 14	lt. 29	lt. 65	lt. 35	lt. 60	lt. 55
Capacità boiler Boiler capacity	lt. 5,5	lt. 8	lt. 9	lt. 8	lt. 9	lt. 9
Temperatura lavaggio/risciacquo Wash/rinse temperature	55°/ 85°	55°/ 85°	55°/ 85°	55°/ 85°	55°/ 85°	55°/ 85°
Durata ciclo Cycle time	120 sec.	120/240 sec.	75/150 sec.	120/240 sec.	120/240 sec. [360 sec.]	60/120/180 sec.
Cicli ora Cycles/hour: up to	30	30/15	48/24	30/15	30/15 [10]	60/30/20
Pressione alimentazione Required water pressure	bar 2 ÷ 4	bar 2 ÷ 4	bar 2 ÷ 4	bar 2 ÷ 4	bar 2 ÷ 4	bar 2 ÷ 4
Ø tubo di carico/scarico (Ø interno) Water supply hose	3/4" / 25	3/4" / 31	3/4" / 31	3/4" / 31	3/4" / 31	3/4" / 31
Acqua alimentazione Supply water	Max 50°C	Max 50°C	Max 50°C	Max 50°C	Max 50°C	Max 50°C
Livello rumorosità Noise emission	< 60 dBA	< 62 dBA	< 60 dBA	< 60 dBA	< 60 dBA	< 62 dBA
Misure cesto tondo Round basket size	Ø 410	—	—	—	—	—
Misure cesto quadro Square basket size	400x400	500x500	500x500	500x500	500x620	500x500
Produzione oraria (bicchieri) Hourly output (glasses) up to	1000÷1200	1500	2400÷1200	1500÷750	—	3000÷1500÷750
Produzione oraria (piatti) Hourly output (dishes) up to	240	540÷270	864÷432	540÷270	—	1080÷540÷360
Peso Netto Net weight	Kg 38	Kg 51	Kg 107	Kg 100	Kg 100	Kg 105